

Third Quarter 2022 Outfall Sampling Rhode Island T.F. Green International Airport

Prepared by: Rhode Island Airport Corporation

October 2022

Background

The Rhode Island Pollutant Discharge Elimination System (RIPDES) permit number RI0021598 issued to Rhode Island TF Green International Airport (PVD)identifies a total of 16 perimeter outfalls. Outfalls 001A, 002A, 003A, 004A and 013A discharge to tributaries of Warwick Pond. Outfalls, 006A, 006B, 006C, 006D, 007A, 007B, 008A and 009A discharge to tributaries of Buckeye Brook downstream of Warwick Pond. Outfalls 010A, 011A, and 012A discharge to Tuscatucket Brook. Major outfalls, 002A, 003A, 008A, and 010A, are those outfalls which receive or may receive drainage from areas where aircraft deicing fluid is applied. Sampling for these major outfalls is defined at Part I.A.1 of the permit. Minor outfalls drain taxiways, runways and other paved services. Outfall 005A was combined with Outfall 006A during construction of Runway 34 Safety Area Improvements. Sampling for these minor outfalls is defined at Part I.A.2. of the permit. Additional sampling requirements are defined at Part I.A.5. and Parts I.C. and I.D. The permit requires quarterly sampling. Table 1 lists parameters sampled for this quarter. Figure 1 identifies outfall and in-stream sampling locations.

Industrial activities at PVD with the potential to impact stormwater quality include the use of glycol-based aircraft deicing and anti-icing fluids (ADFs/AAFs) and pavement deicers. Only propylene glycol (PG) based ADFs/AAFs are used at PVD. Pavement deicers used at PVD include solid sodium formate, and liquid potassium acetate. No aircraft or pavement deicing materials were applied during this quarter.

Summary of Storm

Third Quarter (July 1 through September 30) consists of sampling the major outfalls (002A, 003A, 008A and 010A) hourly for twelve hours.

Light rain began falling just before 10:00 AM on August 22, 2022. Sampling commenced at 12:00 PM (noon) and continued until approximately 11:15 PM August 22, 2022.

A total of 0.23 inches of precipitation (as water equivalent) was measured at PVD during this event with a total of 0.33 inches for the day. Precipitation data measured at PVD and provided by the National Oceanic and Atmospheric Administration's National Climatological Data Center is summarized in Table 2.

Summary of Flow

Flow meters are installed at three of the major outfalls: OF-002A, OF-003A, and OF-008A. Continuous flow measurements during the 12 hours of sampling were made using these Isco 2150 area velocity meters programmed to measure level and velocity and produce flow rate (GPM) at 15 minute increments. No flow meters are installed at minor outfalls or at outfall 010A, as it is off airport property.

Maximum daily and average monthly flows for the major outfalls were calculated and are presented in Table 3. Estimated runoff volumes calculated using drainage area and depth of precipitation for all outfalls are presented in Table 5.

Sample Collection

The laboratory analytical parameters for each sample for the Third Quarter are listed in Table 2. The major outfalls (002A, 003A, 008A, and 010A) were sampled hourly for twelve hours.

Samples were collected and decanted into sample bottles based on the analysis necessary. The bottles were then placed on ice in a cooler for transport to Rhode Island Analytical Laboratories (RIAL) for analysis. Because of the short sample holding time (six hours) for some of the analytical parameters, all samples collected in the first three hours were delivered to the laboratory immediately after the third hour. Samples collected in hours four through twelve were delivered at the completion of sampling.

RIAC also collected and recorded field measurements at each outfall for temperature, pH, specific conductance, and dissolved oxygen (DO).

Sampling Results

Tables 3 and 4 present a summary of analytical results and field measurements expressed as monthly average and maximum daily concentrations for the major outfalls. Table values presented as zero reflect data that was non-detect. Temperature and Oil and Grease are expressed as maximum daily only. pH is expressed as minimum daily and maximum daily.




TABLE 1

LABRATORY ANALYTICAL PARAMETERS
RI T.F. GREEN INTERNATIONAL AIRPORT
WARWICK, RHODE ISLAND
THIRD QUARTER 2022

| Sample Identification | Hours 1-3 | Hours 4-12 |
|--------------------------------|---|---|
| OF-002A, OF-003A, OF-008A, OF- | • Fecal coliform | BOD, Surfactants, Dissolved Oxygen |
| 010A | BOD, Surfactants, Dissolved Oxygen | • pH and Temperature |
| | • pH and Temperature | · COD, TOC |
| | · COD, TOC | Propylene glycol |
| | • Oil & grease -1664, TSS | Dissolved Potassium and Sodium |
| | Propylene glycol | • Total Metals (aluminum, chromium, copper, iron, lead, and zinc) |
| | Dissolved Potassium and Sodium | |
| | Total Metals (aluminum, chromium, copper, iron, lead, and zinc) | |

BOD -Biological oxygen demand COD -Chemical oxygen demand TOC -Total organic carbon TSS -Total suspended solids

TABLE 2 PRECIPITATION AMOUNTS RI T.F. GREEN INTERNATIONAL AIRPORT WARWICK, RHODE ISLAND THIRD QUARTER 2022 August 19 - 22, 2022

| Date | Total Precipitation (water equivalent,in inches) |
|-----------------|--|
| August 19, 2022 | 0.00 |
| August 20, 2022 | 0.00 |
| August 21, 2022 | 0.00 |
| August 22, 2022 | 0.33 |

National Climatic Data Center (NCDC)

https://www.ncdc.noaa.gov/cdo-web/datatools/

TABLE 3 ANALYTICAL RESULTS MAJOR OUTFALLS RI T.F. GREEN INTERNATIONAL AIRPORT WARWICK, RHODE ISLAND THIRD QUARTER 2022

| | | ŀ | | Major Outfalls |) II falle | | | |
|--|--------------|-----------|--------------|----------------------|------------|--------------|-----------|--------------|
| | Outfall 002A | 002A | Outfall 003A | 003A | Outfal | Outfall 008A | Outfal | Outfall 010A |
| Lalali etel | Average | Maximum | Average | Maximum | Average | Maximum | Average | Maximum |
| | Monthly | Daily | Monthly | Daily | Monthly | Daily | Monthly | Daily |
| Flow (gpd) ^{1,8} | 1,775,224 | 8,521,075 | | 2,277,000 10,929,601 | 4,573,007 | 21,950,435 | 7,793,825 | 7,793,825 |
| Oil & Grease (mg/l) ⁵ | | 8.4 | | 1.8 | | 2.1 | | 4.3 |
| TSS (mg/l) ^{4, 5} | 59.0 | 100 | 18.2 | 42.0 | 17.0 | 21.0 | 4.7 | 6 |
| Fecal Coliform (MPN/100ml) 7.5 | 166.0 | 3,500 | 184 | 9,200 | 70,692.0 | 24,000,000 | 181.0 | 540 |
| BOD ₅ (mg/l) ^{2, 5} | 1.8 | 5.3 | 4.9 | 7.1 | 5.6 | 10 | 1.1 | 5.9 |
| Propylene Glycol (mg/l) ^{2, 6} | ND | ND | ND | ND | ND | ND | ND | ND |
| COD (mg/l) ^{2,6} | 1.9 | 21 | 26.4 | 50 | 4.7 | 34 | 3.7 | 20 |
| Dissolved Potassium (mg/l) ^{2, 6} | 3.70 | 5.20 | 4.20 | 5.90 | 4.10 | 7.10 | 11.10 | 32.00 |
| Dissolved Sodium (mg/l) 2 6 | 0.90 | 4.80 | 6.80 | 16.00 | 17.20 | 41.00 | 8.10 | 9.90 |
| Surfactants (ug/l) 2 6 | 232.0 | 380 | 376.0 | 650 | 269.0 | 510 | 82.0 | 240 |
| Dissolved Oxygen (mg/l) 2,3 | 5.73 | 6.39 | 5.95 | 7.13 | 5.64 | 7.29 | 4.81 | 6.57 |
| TOC (mg/l) ^{2 6} | 5.33 | 7.3 | 13.16 | 23 | 7.19 | 13 | 4.22 | 5,8 |
| Total Aluminum (ug/l) 2.6 | 285.4 | 370 | 215.8 | 620 | 347.7 | 710 | 124.8 | 290 |
| Total Chromium (ug/l) 2 6 | 0.7 | 1.8 | 0.9 | 2.5 | 1.6 | 3.6 | 1.4 | 3,4 |
| Total Copper (ug/l) 2,6 | 8.1 | 11 | 19.1 | 37 | 11 | 18 | ND | ND |
| Total Iron (mg/l) ^{2,6} | 24.77 | 39.0 | 3.33 | 14.00 | 5.74 | 9.60 | 1.46 | 2,90 |
| Total Lead (ug/l) 26 | 5.8 | 8.0 | 2.8 | 5.7 | 1.7 | 3.5 | 1.2 | 2.9 |
| Total Zinc (ug/l) 4 ° | 59 | 77 | 36.3 | 150 | 59.5 | 110 | 15.6 | 31 |
| | | | | | | | | |

¹ Results reported as average monthly were determined using the arithmetic average of measurement made every 15 minutes during the 12 hours of sampling. Results reported as maximum daily was the maximum flow measurements over the 12 hours of sampling. Both reported yalves were converted from GPM to GPD reflecting a 24 hour day

² Results reported as maximum daily were the maximum of the 12 samples collected during the 12 hours of sampling.

³ Results reported as average monthly were determined using the artithmetic average of the 12 samples collected during the 12 hours of

³ hours of sampling. Results reported as average monthly were determined using the arithmetic average of the 3 samples collected (when available) during the first

⁵ Results reported as maximum daily were the maximum of the 3 samples collected (when available) during the first 3 hours of sampling

EResults reported as average monthly were determined by using a flow-weighted average of the 12 samples collected during the 12 hours of sampling.

hours of sampling Results reported as average monthly were determined by using a geometric mean of the 3 samples collected (when available) during the 3

⁸ Outfall 010A: Results reported as average monthly and maximum daily were determined using the rainfall amount during the entire storm for the outfall drainage area. BOD₅ - Biological oxygen demand 5-day test

COD - Chemical oxygen demand

gpd - Gallons per day

mg/i - Milligrams per liter

TOC - Total organic carbon

TSS - Total suspended solids

ug/I - Micrograms per liter

RI T.F. GREEN INTERNATIONAL AIRPORT WARWICK, RHODE ISLAND TABLE 4
FIELD ANALYTICAL RESULTS
MAJOR OUTFALLS **THIRD QUARTER 2022**

| 74.5 | | 74.2 | | 71.3 | | 72.6 | | Temperature (°F) |
|--------------------|--------------|--------------------|----------------|--------------------|---------|--------------------|---------|------------------|
| 6.9 | 5.9 | 6.9 | 5.9 | 7.2 | 5.1 | 7.0 | 6.5 | Hd |
| Daily ² | Daily¹ | Daily ² | Daily¹ | Daily ² | Daily¹ | Daily ² | Daily¹ | |
| Maximum | Minimum | Maximum | Minimum | Maximum | muminiM | mumixeM | mnminiM | |
| 010A | Outfall 010A | 1 008A | Outfall 008A | Outfall 003A | Outfal | Outfall 002A | Outfa | Parameter |
| | | | Major Outfalls | Major C | | | | |

Bold text indicates exceedance of permit standards

- ¹ Results reported as minimum daily were the minimum of the samples collected during the 12 hours of sampling.
 ² Results reported as maximum daily were the maximum of the samples collected during the 12 hours of sampling.

TABLE 5 PVD RUNOFF VOLUME CALCULATION RI T.F. GREEN INTERNATIONAL AIRPORT WARWICK, RHODE ISLAND THIRD QUARTER 2022

August 22, 2022

Precip (inches):

0.33

| Drainage Basin ID | Water Discharge | Receiving Water | Drainage Area (ac) | cu ft precip | gal precip |
|----------------------|-----------------|-----------------------|-----------------------|-----------------|------------|
| 1 | Outfall 001A | Warwick Pond | 5.9 | 7,067.6 | 52,866 |
| 2 | Outfall 002A | Warwick Pond | 93.4 | 111,883.9 | 836,891 |
| 3 | Outfall 003A | Warwick Pond | 119.8 | 143,508.4 | 1,073,443 |
| 4 | Outfall 004A | Warwick Pond | 30.1 | 36,056.8 | 269,705 |
| 4B | Outfall 004B | Buckeye Brook | 2 | 2,395.8 | 17,921 |
| 4C | Outfall 004C | Buckeye Brook | 3 | 3,593.7 | 26,881 |
| 6 | Outfall 006A | Buckeye Brook | 10.7 | 12,817.5 | 95,875 |
| 6B | Outfall 006B | Buckeye Brook | 1.5 | 1,796.9 | 13,440 |
| 6C | Outfall 006C | Buckeye Brook | 0.8 | 958.3 | 7,168 |
| 6D | Outfall 006D | Buckeye Brook | 0.7 | 838.5 | 6,272 |
| 7 | Outfall 007A | Buckeye Brook | 9.6 | 11,499.8 | 86,019 |
| 7B | Outfall 007B | Buckeye Brook | 1.2 | 1,437.5 | 10,752 |
| 8 | Outfall 008A | Buckeye Brook | 240.6 | 288,214.7 | 2,155,846 |
| 9 | Outfall 009A | Buckeye Brook | 38.4 | 45,999.4 | 344,075 |
| 10 | Outfall 010A | i uscatucket Brook | 26 | 31,145.4 | 232,968 |
| 11 | Outfall 011A | Tuscatucket Brook | 14 | 16,770.6 | 125,444 |
| 12 | Outfall 012A | Tuscatucket Brook | 46.4 | 55,582.6 | 415,758 |
| 13 | Outfall 013A | Warwick Pond | 28 | 33,541.2 | 250,888 |
| | | TOTAL AREA | 672.1 | 805,108.6 | |